

NAVAL RESEARCH LAB WASHINGTON DC

STABILITY CONSIDERATIONS FOR LIGHT-ION BEAM TRANSPORT IN Z-DISC--ETC(U)

JUL 81 P F OTTINGER, D MOSHER, S A GOLDSTEIN

NL

1 of 1  
40 A  
10'420

■

END  
DATE  
FILMED  
1-81  
DTIC

CO

AD A101426

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

9 REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER NRL Memorandum Report 4548	2. GOVT ACCESSION NO. AD-A207 426	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) STABILITY CONSIDERATIONS FOR LIGHT-ION BEAM TRANSPORT IN Z-DISCHARGE CHANNELS	5. TYPE OF REPORT & PERIOD COVERED Interim report on a continuing NRL problem	6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) P.F. Ottinger, D. Mosher, and A.A. Goldstein*	8. CONTRACT OR GRANT NUMBER(s) 1112 J01 87	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Research Laboratory Washington, D.C. 20375	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Sponsor Assignment No. DE-A108-79DP40092 NRL Prob 47-0879-0-1	
11. CONTROLLING OFFICE NAME AND ADDRESS Department of Energy Washington, D.C. 20545	12. REPORT DATE July 8, 1981	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) 14) NRL-MR-4548	13. NUMBER OF PAGES 25	15. SECURITY CLASS. (of this report) UNCLASSIFIED
	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE	
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES *Present address: Jaycor, Inc., Alexandria, VA 22304		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) intense ion beams transport instabilities z-discharge channels		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Light-ion beams, appropriate for use as inertial-confinement fusion drivers, can be transported in z-discharge channels over distances of several meters. Here stability considerations for light-ion beam transport in such channels are reviewed. Many aspects of the important velocity-space instabilities are considered and the resulting conditions for good transport are discussed. The results will be presented in a general form so that they may be applied to beams of various species (e.g. H <sup>+</sup> , D <sup>+</sup> , C <sup>4+</sup> , etc.) propagating in channel plasmas of different composition (e.g. hydrogen, argon, air, etc.).		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE  
S/N 0102-014-6601

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

## CONTENTS

1. INTRODUCTION . . . . .	1
2. BEAM-PLASMA SYSTEM IN THE TRANSPORT CHANNEL . . . . .	2
3. LINEAR STABILITY ANALYSIS . . . . .	3
3.1. <u>ES Modes</u> . . . . .	4
3.1a. <u>e-b Two Stream Mode</u> . . . . .	4
3.1b. <u>e-i Two Stream Mode</u> . . . . .	5
3.1c. <u>Ion-Acoustic Mode</u> . . . . .	5
3.1d. <u>ES Stability Conditions</u> . . . . .	6
3.2. <u>EM Modes</u> . . . . .	6
3.2a. <u>Beam-Whistler Mode</u> . . . . .	6
3.2b. <u>Beam-Weibel Mode</u> . . . . .	7
3.2c. <u>Plasma-Electron Mode</u> . . . . .	7
3.2d. <u>EM Stability Conditions</u> . . . . .	8
4. CONCLUSIONS . . . . .	9
5. REFERENCES . . . . .	10

Accession For	
N11S GR&I	<input checked="" type="checkbox"/>
LTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	<input type="checkbox"/>
By	
Distribution/	
Availability Codes	
Dist	Avail and/or
A	Special

## STABILITY CONSIDERATIONS FOR LIGHT-ION BEAM TRANSPORT IN Z-DISCHARGE CHANNELS

### 1. INTRODUCTION

The development of terawatt-level ion beams has generated a great deal of interest in using light-ion beams to drive thermonuclear pellets.<sup>1-9</sup> Target design studies for light-ion beams indicate that  $\sim 2$  MJ of ions must be delivered in  $\sim 10$  nsec to an  $\sim 1$  cm diameter pellet in order to achieve high-gain thermonuclear ignition.<sup>10</sup> Since present technology can provide up to 5 TW single-generator modules from which up to 200 kJ of ions can be extracted in  $\sim 50$  nsec, a multimodule system is required. In addition, a transport scheme and a method for beam pulse compression are needed.

One possible transport scheme involves the use of a z-discharge channel for transporting a prefocused ion beam (Fig. 1).<sup>11</sup> Focusing is achieved by a combination of geometric and magnetic-field focusing prior to injection into the channel.<sup>12,13</sup> Beam pulse compression results from ramping the diode voltage such that the tail of the beam catches up to the front of the beam.<sup>13,14</sup> The ideal diode voltage waveform is  $\phi(t) = \phi_0(1-t/t_a)^{-2}$  for  $0 \leq t \leq \tau_b < t_a$  where  $\tau_b$  is the beam pulse duration and  $t_a$  is the beam arrival time at the target.

Assuming that the z-discharge channel is produced in a MHD stable configuration, the question of the effects that the passage of the beam will have on the equilibrium and stability of the beam-plasma system is an important one. The MHD response of the plasma has been treated elsewhere<sup>15</sup> and will only be briefly reviewed here. Analysis of stable beam propagation in straight and tapered channels, as well as in bumpy channels (subject to sausage instability) has also been done previously.<sup>16</sup> This work shows that, in the absence of microinstabilities driven by the beam, good beam transport and bunching is possible under the conditions set by MHD considerations (which will be outlined in Sec. 2). However, in the presence of microinstabilities, beam transport and bunching can be seriously affected.

Analysis of electrostatic (ES)<sup>17</sup> and electromagnetic (EM)<sup>18</sup> velocity-space instabilities, which can grow on a time scale much faster than the beam pulse duration, will be reviewed in this report. The problem will be considered with the goal of identifying the conditions for good transport and bunching. The results will be presented in a general form so that they may be applied to beams of various low atomic number species propagating in channel plasmas of different compositions.

## 2. BEAM-PLASMA SYSTEM IN THE TRANSPORT CHANNEL

The beam-plasma system consists of a focused ion beam propagating down the axis of an externally-driven z-discharge plasma channel.<sup>13,19</sup> The ion beam is focused at the entrance to the plasma channel (see Figs. 1 and 2) with velocity components transverse to z given by  $V_{\perp}/V_z = \tan \alpha \ll 1$ . The current being driven in the preformed z-discharge channel provides the radial confinement of the beam. Because of the small perpendicular beam energy, the channel current can be much less than the beam current. A high plasma density in the channel insures good beam charge neutralization.<sup>20</sup> Good beam current neutralization in the interior of the beam also occurs, so that the total magnetic field is comparable to that associated with the preformed channel established before beam injection. Because  $J_p = J_{ch} - J_b \approx -J_b$ , the electron drift velocity is approximated by  $V_e \approx n_b Z_b V_b / Z_p n_p$ , where  $n_b$  and  $n_p$  are the beam and plasma ion densities,  $Z_b$  and  $Z_p$  are the beam and plasma ion charge states, and  $J_p$ ,  $J_b$  and  $J_{ch}$  are the plasma, beam and preformed channel current densities, respectively. Note that the electron density is  $Z_p n_p$ .

Hydrodynamic modeling of the background plasma<sup>15</sup> shows that a uniform net-current model is appropriate for the early times associated with passage of the beam front. This is because the low-temperature channel is established microseconds before beam injection so that complete magnetic diffusion occurs. Later in the ion pulse,  $J_p \times B$  expansion of the beam-heated high-temperature plasma reduces the magnetic field strength in the interior of the channel. The built-up field in the expanding cylindrical shock wave is also enhanced by significant current non-neutralization in the cool plasma surrounding the beam-heated channel. The maximum field strength just outside the ion-beam radius can exceed that established by the preformed z-discharge current by a large factor. Thus, at late times during beam passage, the magnetic field distribution can be approximated by a surface-current model. Although the induced  $V_r \times B_0$  electric field is important when considering beam energy losses during transport, at no time does the electric field become large enough to significantly affect the stability analysis.

The linearized stability analysis presented here strictly applies only when the mode under consideration grows on a time scale faster than any changes in the beam-plasma system (i.e.,  $\gamma > \tau_b^{-1}$ ). For growth on a time scale slower than the beam pulse duration, the perturbation analysis breaks down since small perturbations will be washed out by the zero-order changes in the system before growth can occur. Thus for those modes which are shown to e-fold less than once during the passage of the beam, the results should be interpreted as showing that significant growth does not occur.

The distribution of particles in axial velocity is illustrated in Fig. 3. The plasma ions form a stationary background while the drift of the plasma electrons provides for beam current neutralization. Because of the high plasma density, this drift velocity,  $V_e$ , does not exceed the electron thermal velocity even before the beam heats the plasma. As the beam passes through a given point, the plasma is heated and the conductivity increases. The electron-ion collision frequency,  $\nu_{ei}$ , decreases but the electrons generally remain collisional ( $\nu_{ei} > \omega_{ce}$ ) at all times during the pulse for purposes of the stability analysis. Since the electron-ion equilibration time is on the order of the beam pulse duration the electron temperature will not exceed the ion temperature by more than a factor of ten.

The ion beam density is typically much less than the plasma density and, beams of interest are nonrelativistic. The spread in axial velocities, designated by  $V_t$  in Fig. 3, is on the order of  $V_b \alpha_m^2/2$  before beam bunching occurs. Here  $V_b$  is the beam velocity and  $\alpha_m$  is the maximum ion injection angle into the channel. For  $\alpha_m = 0.1-0.2$  rad,  $V_t/V_b$  is relatively small. As the beam bunches,  $V_t/V_b$  can increase by an order of magnitude as the faster ions generated later in the pulse catch up to slower ions at the front of the beam. The beam pulse duration,  $\tau_b$ , decreases and the beam density,  $n_b$ , increases as the beam bunches. The dependence of the beam parameters on axial position due to bunching will be expressed explicitly as  $V_t(z)$ ,  $\tau_b(z)$ , etc.

Since the ES stability analysis depends strongly on the shape of the beam distribution function, it is important to use a theoretical model which contains the appropriate physics. For a distribution in  $v_z$  which has a large slope on the low velocity side such as illustrated in Fig. 4a, a resistive instability persists in spite of the thermal spread in  $v_z$  and the high frequency of collisions between the plasma electrons and ions.<sup>21,22</sup> However, if the slope of the distribution function is not as sharp, such as for the Gaussian distribution shown in Fig. 4b, electron-ion collisions are damping if the thermal spread in  $v_z$  is sufficiently large. The slope of the distribution function on the high velocity side does not affect the stability analysis.

Before the beam bunches, the distribution in  $v_z$  is determined by the injection condition. Since the ions are injected into the channel nearly uniformly over a range of angles predominately in the  $r$ - $z$  plane and since the time-averaged axial velocity for an ion injected at a given  $\alpha$  varies like  $V_t(1-\alpha^2/2)$ , the distribution in  $v_z$  rises slowly as indicated in Fig. 4c. Additional smoothing out of the distribution in  $v_z$  will result from beam energy spreading due to radial variations in the diode voltage. The stability properties of this distribution closely resemble those of the Gaussian distribution. The beam ion distribution after bunching is also similar in shape to Fig. 4c. Since the ion diodes which are used in the experiments have a constant impedance behavior during the duration of the ion pulse, more ions (higher currents) are generated at higher energies as the diode voltage ramps upward. Thus in the bunched state there are more ions at higher velocities than at lower velocities and the spread in axial velocities is on the order of  $(2Z_d e/m_i)^{1/2}(\phi_f^{1/2} - \phi_0^{1/2})$ . Here  $Z_d$  is the charge state of the beam ions in the diode and  $\phi_0$  and  $\phi_f$  are the initial and final diode voltages. This spread can be considerably larger than the initial spread before bunching ( $V_t \sim V_b \alpha_m^2/2$ ).

Thus a Gaussian distribution can be used to properly model the ion beam distribution function both before and after bunching when considering ES modes. When the analysis is not sensitive to the detailed shape of the distribution function (e.g. for analyzing the stability of EM modes), simpler models may be used.

### 3. LINEAR STABILITY ANALYSIS

The results of linear stability analyses reported previously<sup>17,18,22</sup> are presented here in a more general form so that they may be applied to beams of various species. The composition of the channel plasma is also unspecified. Growth rates will vary as the beam heats the channel plasma and as the channel expands. The changes in the hydrodynamic structures of

the channel occur gradually over the pulse duration of the beam. Growth rate expressions appropriate near both the front and the tail of the beam are presented in order to determine how hydrodynamic changes alter the results. Most notably these changes include (1) a reduction in the e-i collision frequency at the tail of the beam where the plasma is heated, and (2) a reduction in the magnetic field in the interior of the channel at late times in the pulse as the now highly conducting heated plasma expands due to  $\mathbf{J} \times \mathbf{B}$  forces. Near the front of the beam, the beam ions follow betatron-like orbits while at the tail of the beam, the beam ions move in more straight line-like orbits with reflections off of the magnetic field piled up at the edge of the channel.

### 3.1. ES Modes

The ES modes are the fastest growing modes when driven unstable. Unstable growth will generally reach nonlinear saturation on a time scale much faster than the beam pulse duration. These modes involve either charge bunching (e-b and e-i modes) or density bunching (ion-acoustic mode) and generally exhibit their largest growth for  $\mathbf{k} = k\hat{z}$ , which is a result of the small thermal spread in the axial direction before axial beam compression occurs.

#### 3.1a. e-b Two Stream Mode

The e-b two stream instability is driven by the relative streaming between the beam ions and plasma electrons. In general the beam can be considered warm because  $V_t(z)/V_b \geq 2[m_e Z_p^2 n_b(z)/m_b Z_p n_p]^{1/3}$  even before beam bunching occurs. Here  $m_b$  is the beam ion mass. Near the front of the beam the betatron motion of the ions can reduce the growth rate of the mode which is given by

$$\gamma_1 = -\frac{\nu_{ei}}{2} + 0.76 \frac{\omega_{pb}^2(z)}{\omega_{pe}} \left( \frac{V_b}{V_t(z)} \right)^2 R \quad (1)$$

where  $\omega_{pb}^2 = 4\pi e^2 Z_p^2 n_b(z)/m_b$  and  $\omega_{pe}^2 = 4\pi e^2 Z_p n_p/m_e$  are the beam and electron plasma frequencies respectively. The electron-ion collision frequency is given by  $\nu_{ei} = 1.45 \times 10^{-6} Z_p^2 n_p \lambda_{ei}/T_e^{3/2}$ , where  $T_e$  is in eV and  $\lambda_{ei}$  is the Coulomb logarithm. The reduction factor,  $R$ , equals the fraction of beam ions which can effectively participate in the wave growth. If  $\gamma_1 > 2\omega_\beta$ , which is the usual case, all ions can participate and  $R = 1$ . Here  $\omega_\beta = (V_b \omega_{cb}/r_c)^{1/2}$  is the ion betatron frequency and  $\omega_{cb}$  is the beam cyclotron frequency. If  $\gamma_1 \leq 2\omega_\beta$ , only those ions with  $\Delta z < 1/k$  can participate, where  $\Delta z$  is the amplitude of the betatron oscillations about  $z = \bar{v}_z t$  (see Fig. 5). The amplitude,  $\Delta z$ , depends on the ion injection conditions,  $r(z=0)$  and  $\alpha(z=0)$ .<sup>17</sup> If this amplitude is large, the ion moves across many wave fronts before the instability e-folds even once, and thus cannot effectively participate in wave growth. The value of  $R$  must be calculated from the actual distribution function. For a Gaussian distribution  $R \sim 8\omega_\beta V_b/kV_t^2$  for  $k > 8\omega_\beta V_b/V_t^2$  and  $R = 1$  for  $k < 8\omega_\beta V_b/V_t^2$ . At the tail of the beam, betatron effects are less important, so that  $R = 1$  in Eq. (1).



Beam heating of the plasma can considerably reduce the damping term in Eq. (1) as e-i collisions become less frequent. Beam bunching, on the other hand, reduces the driving term in Eq. (1) as  $V_t$  increases dramatically. Thus the potentially most dangerous position for wave growth lies at the tail of the beam ( $R=1$ ) at the beginning of the transport channel before significant beam bunching occurs.

### 3.1b. e-i Two Stream Mode

The e-i two stream mode is driven by the relative streaming between the background electrons and ions. The electrons drift with an average velocity  $V_e \sim n_b Z_b V_b / Z_p n_p$  relative to the stationary ions and in general  $V_e < u_e$ . Here  $u_e$  is the thermal velocity of the electrons. The expression for the growth (damping) rate is

$$\gamma = -\nu_{ei} - (\pi/8)^{1/2} \frac{kc_s}{(1+k^2\lambda_{De}^2)^2} \left\{ Z_p (T_e/T_i)^{3/2} \exp\left[-\frac{T_e}{2T_i(1-k^2\lambda_{De}^2)}\right] + \frac{m_e}{m_i} \left(1 - \frac{V_e}{c_s} [1+k^2\lambda_{De}^2]^{1/2}\right) \right\} \quad (2)$$

where  $c_s = (T_e/m_i)^{1/2}$  is the ion sound speed,  $\lambda_{De} = (T_e/4\pi e^2 Z_p n_p)^{1/2}$  is the electron Debye length and where a simple Krook model was used for the collision term. In deriving Eq. (2), it was assumed that  $\nu_{ei} < kc_s/(1+k^2\lambda_{De}^2)^{1/2}$ . When  $T_e \sim T_i$  this reduces to

$$\gamma_2 \approx -\nu_{ei} + (\pi/8)^{1/2} \frac{kc_s}{(1+k^2\lambda_{De}^2)^{3/2}} \left\{ \frac{V_e}{u_e} - \frac{Z_p \exp\left[-\frac{1}{2(1+k^2\lambda_{De}^2)}\right]}{(1+k^2\lambda_{De}^2)^{1/2}} \right\} \quad (3)$$

Since  $V_e$  is usually less than  $u_e$ , the mode is typically stable.

### 3.1c. Ion-Acoustic Mode

If  $T_e \gg T_i$ , then the drifting electrons can drive an ion-acoustic instability. In this case Eq. (2) reduces to

$$\gamma_3 \approx -\nu_{ei} + \left(\frac{\pi m_e}{8 m_i}\right)^{1/2} \frac{k}{(1+k^2\lambda_{De}^2)^{3/2}} \left[ V_e - \frac{c_s}{(1+k^2\lambda_{De}^2)^{1/2}} \right] \quad (4)$$

This predicts instability ( $\gamma > 0$ ), if  $V_e/c_s > (1+k^2\lambda_{De}^2)^{-1/2}$  and if  $\nu_{ei}$  is sufficiently small. However, the severity of the condition on  $T_e/T_i$  is often overlooked. For  $V_e/c_s$  as large as 5,  $T_e/T_i$  must be greater than 12 for instability even for  $k\lambda_{De} \ll 1$ . Figure 6 shows the critical values of  $T_e/T_i$  for instability versus  $k$  for various values of  $V_e/c_s$  (assuming  $\nu_{ei} = 0$ ). Since  $T_e/T_i$  is not expected to reach such high levels, in general ion-acoustic turbulence is not expected.

### 3.1d. ES Stability Conditions

Since the e-b mode is the only ES instability which could be generated, it is important to state under which conditions it may be avoided. For stability ( $\gamma_1 \leq 0$ ) Eq. (1) states that

$$\frac{Z^{5/2} n_p^{3/2} \lambda_{ei}}{T_e^{3/2}} \geq 3.2 \times 10^7 \frac{Z_b^2 n_b(z) v_b^2}{\mu_b v_t^2(z)} \quad (5)$$

is required. Here  $\mu_b = m_b/m_H$ ,  $T_e$  is measured in eV and all other variables are in Gaussian units. This condition used in conjunction with the condition

$$n_p \approx 1.4 \times 10^{12} I_{ch}^{-2} (I_b(z) \tau_b(z)/S)^{1/2}, \quad (6)$$

derived from MHD considerations<sup>15</sup>, set constraints on  $n_p$  and  $T_e$  for good transport. Here  $I_{ch}$  and  $I_b$  are measured in amps and  $S$  is the beam stopping power of the plasma measured in erg·cm<sup>2</sup>/g. Eq. (6) gives the ion density in the channel required for minimum beam energy loss in the channel during transport. Given this required ion density, Eq. (5) sets an upper limit on  $T_e$ , beyond which electrostatic turbulence will set in. For good transport both of these conditions must be satisfied. Generally the stability criterion in Eq. (5), is most severely tested at the tail of the beam where  $T_e$  is largest and at the beginning of the transport channel before significant bunching occurs where  $V_t(z)$  is smallest ( $V_t(z)/V_b \sim \alpha_m^2/2$ ).

### 3.2 EM Modes

The EM modes are slower growing modes than the ES modes, so that even if the mode is unstable, growth may not have sufficient time to reach non-linear saturation during the pulse duration of the beam. The modes are nearly purely growing (i.e. do not convect with the beam) and involve current bunching or filamentation of the beam and/or plasma channel. The wave vector,  $\vec{k}$ , is oriented perpendicular to the direction of beam propagation with  $k = k\hat{e}_r$  for the Weibel mode (radial current bunching) and  $k = k\hat{e}_\theta$  for the whistler mode (azimuthal current bunching). In addition, the cylindrical geometry dictates that  $k_r \geq 2\pi/r_b$  and  $k_\theta \geq \ell/r_b$  where  $\ell$  is an integer.

#### 3.2a. Beam-Whistler Mode

The beam-whistler instability is driven unstable by the relative streaming motion between the beam ions and the channel plasma. Since the wave vector is in the azimuthal direction and the beam ions execute their betatron orbits in the r-z plane, the betatron motion of the beam has little effect on the mode. However, a small spread in angular momentum, which is observed experimentally, can reduce the growth rate significantly. With no spread in angular momentum ( $V_\theta^2/c^2 < 2v_{ei}\omega_{pb}V_b/c\omega_{pe}^2$ ) the growth rate is

$$\gamma = \omega_{pb}(z)V_b/c, \quad (7)$$

and with  $V_\theta^2/c^2 > 2v_{ei}\omega_{pb}(z)V_b/c\omega_{pe}^2$  the peak growth rate is

$$\gamma_4 = 2v_{ei}\omega_{pb}^2(z)V_b^2/V_\theta^2\omega_{pe}^2 \quad (8)$$

at  $k \sim \gamma_4/V_b$ . Here  $V_\theta$  is a measure of the thermal spread in the azimuthal velocity of the beam ions. If  $kr_b < 1$ , peak growth rate is reduced to  $[1-(k_0r_b)^{-2}]\gamma_4$  because of geometry constraints and if  $k_0r_b < 1$ , no growth is possible. The critical wavenumber  $k_0 = \sqrt{2}\omega_{pb}(z)V_b/cV_\theta$  [see Eq. (35), Ref. 18].

If there is wave growth at a given point in  $z$ , the number of e-folds that occurs is just

$$N = \int_0^{\tau_b(z)} \gamma(t) dt, \quad (9)$$

where the time dependence of the plasma parameters must be considered. Most importantly  $v_{ei}$  decreases at  $T_e^{-3/2}(t)$  as the plasma is heated by the passing beam. Note that beam thermal effects do not completely quench the instability because of the finite plasma resistivity. Given information from MHD considerations on the time variation of the plasma parameters due to beam passage, one can then determine from Eq. (9) whether significant azimuthal beam current bunching occurs.

### 3.2b. Beam-Weibel Mode

For the beam-Weibel instability the wave vector is in the radial direction. In this case the spread in perpendicular velocities associated with the betatron motion of the beam ions reduces the growth rate of the instability. A measure of the radial velocity spread is given by  $V_0\alpha_m$ , so that the peak growth rate is given by

$$\gamma_5 = 2^{4/5}v_{ei}\omega_{pb}^2(z)/\omega_{pe}^2\alpha_m^{8/5} \quad (10)$$

at  $k \sim \gamma_5/V_b\alpha_m^{7/5}$ . Again the number of e-folds that occur at a given point in  $z$  can be determined by Eq. (9) and MHD considerations. Since the thermal spread in the radial velocity is typically comparable or larger than the thermal spread in the azimuthal velocity, the beam-Weibel instability is generally less dangerous than the beam-whistler mode. A superposition of both unstable modes, however, will lead to beam filamentation.

### 3.2c. Plasma-Electron Mode

If beam thermal effects or geometry constraints prevent the beam from driving strong EM wave growth, instability can still result from the electron return current established with the plasma. Because of the high collisionality ( $v_{ei} > \omega_{ce}$ ) of the plasma electrons, radial ( $\vec{k} = k\hat{e}_r$ ) and azimuthal ( $\vec{k} = k\hat{e}_\theta$ ) EM modes driven by the plasma electrons are essentially indistinguishable (aside from small geometric effects). The analysis must include electron thermal effects, as well as collisional effects since the

electron streaming velocity is subthermal even early in the pulse before beam heating occurs.

At early times in the pulse when  $\omega_{pe} u_e / c v_{ei} > 1$ , the peak growth rate is

$$\gamma = (\omega_{pi} V_e / c) (2 - Z_p^{-1})^{1/2} \quad (11)$$

Later in the pulse after the beam heats the plasma if  $\omega_{pe} u_e / c v_{ei} > 1$ , then thermal effects slows the growth of the mode. The maximum growth rate is then given by

$$\gamma = 2^{-3/2} \omega_{pe} V_e^2 / c u_e \quad (12)$$

At all times in the pulse geometry constraints prevent wave growth if  $k_{orb} < 1$  where in this case  $k_o = \omega_{pe} V_e / \sqrt{2} u_e c$ . Since again this mode does not convect, the number of e-folds at a given point in  $z$  can be obtained from Eqs. (11), (12) and (9) and MHD considerations.

### 3.2d. EM Stability Conditions

If the growth rates of the EM instabilities are slow enough such that less than one e-fold ( $N < 1$ ) occurs during beam passage, wave growth will be washed out by the MHD changes in the beam-plasma system. Only wave growth with  $N > 1$  will affect beam transport. In order to prevent the beam from filamenting, the beam should then have

$$\alpha_m^2 \geq V_\theta^2 / V_b^2 > 1.6 \times 10^{-9} \frac{n_b(z)}{\mu_b} \int_0^{\tau_b(z)} \left( \frac{Z_p \lambda_{ei}}{T_e^{3/2}} \right) dt \quad (13)$$

where again  $T_e$  is in eV's and  $n_b$  is measured in  $\text{cm}^{-3}$ . This condition is derived from Eq. (8) for azimuthal current bunching which is typically more severe than the condition for radial current bunching since  $\alpha_m$  is usually greater than  $V_\theta / V_b$ . Here it is also assumed that  $\sqrt{2} \omega_{pb}(z) r_b V_b / c V_\theta > 1$ , which is the usual case. In order to evaluate Eq. (13), a knowledge of the MHD response to beam passage is required, in particular, one must know the time history of the electron temperature.

If the beam is warm enough to prevent beam filamentation (i.e., Eq. (13) is satisfied), it is still possible for the channel to filament. Channel filamentation is avoided if

$$\frac{J_b(z)}{n_p^{1/2}} \left( \frac{9.4 \times 10^1}{\mu_p^{1/2}} \int_0^{t_1(z)} (2 - Z_p^{-1}) dt + 6.9 \times 10^4 J_b(z) \int_{t_1(z)}^{\tau_b(z)} \frac{dt}{t(z) n_p z^{3/2} T_e^{1/2}} \right) \leq 1 \quad (14)$$

Here  $\mu_p = m_p / m_H$ ,  $J_b(z) = Z_p n_b(z) V_b$ ,  $J_b$  is measured in  $\text{SA/cm}^2$  and  $t_1$  is defined as the time it takes for the beam to heat the plasma

to  $T_e^1 = 1.4 \times 10^{-4} (Z_p^3 t_1 n_p \lambda_{ei}^2)^{1/4}$  in eV. If  $T_e(0) > T_e^1$ , then  $t_1 = 0$  and the first term in Eq. (14) does not contribute. If  $t_1 \geq \tau_b$ , then the second term in Eq. (14) does not contribute and the limits on the integration of the first term go from 0 to  $\tau_b(Z)$ . In Eq. (14) it was assumed the  $\omega_{pb} v_e / 2u_{ec} > 1$ , which is the usual case. Eq. (14) sets an upper limit on transportable beam current density above which channel filamentation will develop.

#### 4. CONCLUSIONS

The stability conditions in Eqs. (5), (13) and (14), identify important constraints on beam propagation. Eq. (5) together with Eq. (6) states that the plasma cannot be heated above a certain critical temperature without generating electrostatic microturbulence. Such turbulence will degrade beam quality and confinement. In general the most severe constraint on  $T_e$  exists at the tail of the beam before bunching occurs where the critical temperature is defined by

$$T_e^c (\text{eV}) \equiv 10^{-6} \left( \frac{\mu_b^2 n_p^3 Z_p^5 \lambda_{ei}^2 \alpha_m^8}{Z_b^4 n_b^2 (z=0)} \right)^{1/3}, \quad (15)$$


where  $n_p$  is given in Eq. (6). By increasing  $n_p$  the critical temperature can be raised at the expense of increasing the beam energy loss during transport. Operating at twice the density specified in Eq. (6) increases  $T_e^c$  by a factor of two but only increases the beam energy loss by 25%. The actual temperature that the electrons will reach for a given beam and background gas is not always easily estimated and must be calculated on a case to case basis and compared with the critical temperature defined in Eq. (15). Here  $\alpha_m$  is a measure of the spread in axial velocities in the beam, which for a monoenergetic beam is given by  $\Delta V_z / V_b \sim \alpha_m^2 / 2$ . If the beam has a spread in energy such that  $\alpha_m^2 < \Delta E / E$ , then  $\alpha_m^8$  in Eq. (15) should be replaced by  $(\Delta E / E)^4$ .

Growth of electromagnetic waves can be held to a tolerable level by allowing for a reasonable spread in beam perpendicular energy and limiting the beam current density. If the beam is too cold, beam filamentation can occur during beam transport. The condition for good beam transport is given in Eq. (13). If the beam does not filament but the beam current density is too high, the return current in the channel can cause channel filamentation. In order to prevent this from occurring Eq. (14) should be satisfied. The conditions given in Eqs. (13) and (14) may actually be too severe since channel hydrodynamic effects have not been included self consistently in the analysis. Channel expansion due to  $J \times B$  force may tend to prevent growth of these transverse modes. These effects are presently under investigation.

## 5. REFERENCES

1. S. A. Goldstein and R. Lee, Phys. Rev. Lett. 35, 1079 (1975).
2. J. W. Poukey, J. R. Freeman, M. J. Clauser, and G. Yonas, Phys. Rev. Lett. 35, 1806 (1975).
3. J. W. Poukey, J. Vac. Sci. Technol. 12, 1214 (1975)
4. A. E. Blaugrund, G. Cooperstein, J. R. Boller and S. A. Goldstein Bull. Am. Phys. Soc. 20, 1252 (1975).
5. P. A. Miller, C. W. Mendel, D. W. Swain, and S. A. Goldstein, in Proceedings of the International Topical Conference on Electron Beam Research and Technology, Albuquerque, New Mexico (1975), p. 619.
6. G. Cooperstein, S. J. Stephanakis, J. R. Boller, R. Lee, and S. A. Goldstein, in Proceedings of the 1976 IEEE International Conference on Plasma Science, Austin, Texas (IEEE, New York, 1976), p. 126.
7. D. J. Johnson, G. W. Kuswa, A. V. Farnsworth, Jr., J. P. Quintenz, R. J. Leeper, E. J. T. Burns, and S. Humphries, Jr., Phys. Rev. Lett. 42, 610 (1979); D. J. Johnson, Bull. Am. Phys. Soc. 24, 925 (1979).
8. G. Cooperstein, S. A. Goldstein, D. Mosher, W. F. Oliphant, F. L. Sandel, S. J. Stephanakis and F. C. Young in Proceedings Third International Topical Conference on High Power Electron and Ion Beam Research and Technology, Novosibirsk, USSR (1979).
9. G. Cooperstein, S. A. Goldstein, D. Mosher, R. J. Barker, J. R. Boller, D. G. Colombant, A. Drobot, R. A. Meger, W. F. Oliphant, P. F. Ottinger, F. L. Sandel, S. J. Stephanakis and F. C. Young, in Laser Interaction and Related Plasma Phenomena, edited by H. Schwarz, H. Hora, M. Lubin and B. Yaakobi, (Plenum Press, New York, 1980).
10. R. O. Bangerter and D. J. Meeker, in Proceedings of the Second International Topical Conference on High Power Electron and Ion Beam Research and Technology, Ithaca, New York (1977), p. 183; J. H. Nuckolls, in Proceedings of the Topical Meeting on ICF (Opt. Soc. of Am. Wash., DC, 1978) paper TuA5.
11. S. A. Goldstein, D. P. Bacon, D. Mosher and G. Cooperstein Proceedings of the Second International Topical Conference on High Power Electron and Ion Beam Research and Technology, Ithaca, New York (1977), p. 71.
12. D. Mosher, G. Cooperstein, S. A. Goldstein, in Digest of the Topical Meeting on ICF (Opt. Soc. of Am., Wash., DC, 1980), paper ThC5.
13. D. Mosher, Bull. Am. Phys. Soc. 24, 926 (1979).
14. D. Mosher and S. A. Goldstein, Bull. Am. Phys. Soc. 23, 800 (1978).

15. D. G. Colombant, D. Mosher and S. A. Goldstein, Phys. Rev. Lett. 45, 1253 (1980).
16. P. F. Ottinger, D. Mosher and S. A. Goldstein, Phys. Fluids 23, 909 (1980).
17. P. F. Ottinger, D. Mosher and S. A. Goldstein, Phys. Fluids 22, 332 (1979).
18. P. F. Ottinger, D. Mosher and S. A. Goldstein, Phys. Fluids 24, 164 (1981).
19. F. Sandel, G. Cooperstein, S. A. Goldstein, D. Mosher and S. J. Stephanakis, Bull. Am. Phys. Soc. 24, 1031 (1979).
20. D. A. Hammer and N. Rostoker, Phys. Fluids 13, 1831 (1970).
21. B. S. Newberger and L. E. Thode, Bull. Am. Phys. Soc. 24, 1097 (1979).
22. P. F. Ottinger, Conference Record-Abstracts of the 1980 IEEE International Conference on Plasma Science, Madison, Wisconsin (IEEE, New York, 1980), p. 57.
23. V. U. Abramovich and V. I. Sevchenko. JETP 35, 730 (1972).
24. P. F. Ottinger, S. A. Goldstein and D. Mosher, NRL Memorandum Report 4180 (1980).




IDEAL DIODE VOLTAGE WAVEFORM:

$$\phi(t) = \frac{\phi_0}{(1 - t/t_a)^2} ; \quad 0 \leq t \leq \tau_b < t_a$$


Fig. 1—Schematic of ion diode, focusing region and transport channel for light ion beam ICF module. The ideal diode voltage waveform for axial bunching is also shown where  $\phi_0$  is the initial diode voltage,  $t_a$  is the beam arrival time at the target and  $\tau_b$  is the beam pulse duration at injection.





$$I_{ch} (A) = (3.2 \times 10^7 \mu_b Z_b^{-1} \alpha_m^2 V_b / c)$$

Fig. 2—Schematic of beam propagation in a z-discharge channel. Here  $\frac{1}{2} m_i V_b = Z_d e \phi$  (where  $Z_d$  is beam ion charge state in the diode and  $\phi$  is the diode voltage),  $\alpha_m$  is the maximum injection angle,  $r_s$  is the beam spot size (or aperture size) and  $r_b$  is the beam radius in the channel. Also shown is the channel current required to confine the beam where  $Z_b$  is the charge state of the beam ions in the channel and  $\mu_b = m_b / m_H$ .



PLASMA:

$$T_e \gtrsim T_i$$

$$\nu_{ei}(T_e) > \omega_{ce}$$

$$V_e \approx Z_b n_b V_b / Z_p n_p < (T_e / m_e)^{1/2}$$

BEAM:

$$V_b / c \ll 1$$

$$n_b \ll n_p$$

$$\frac{V_t}{V_b} \approx a_m^2$$

Fig. 3—Schematic of particle distribution in  $v_z$ . Here  $i$ ,  $e$  and  $b$  are the plasma ions, plasma electrons and beam ions, respectively, and  $V_t$  is the measure of the spread in the beam distribution. Other typical beam-plasma conditions are also listed.






Fig. 4-- Distribution of beam ions in  $v_z$  for (a) a uniform distribution, (b) a Gaussian distribution actual distribution and (c)




Fig. 5—Beam ion orbits in a frame of reference moving with the phase velocity of an ES wave




Fig. 6—Critical values of  $T_e/T_i$  for ion-acoustic instability (assuming  $\nu_{ei} = 0$ ). Regions above the curves are unstable and below the curves are stable.

# DISTRIBUTION LIST

APRIL 1951

Director  
Defense Intelligence Agency  
Washington, DC 20301

Attn: DTIC Robert I. Rubenstein 1 copy

Defense Advanced Research Project Agency  
1400 Wilson Blvd.  
Arlington, VA 22209  
Attn: J. Dayless 1 copy

Director  
Defense Nuclear Agency  
Washington, DC 20305

Attn: FCPR 1 copy  
SIVL 1 copy  
TISI Archives 1 copy  
TILL Tech. Library 3 copies  
J. Z. Farber (DAFV) 1 copy  
R. L. Gullickson (DAFV) 1 copy

Defense Technical Information Center  
Cameron Station  
5010 Duke Street  
Alexandria, VA 22314

Attn: T. C. 12 copies

Under Sec'y of Defense for RSCH and ENGRG  
Department of Defense  
Washington, DC 20301

Attn: SSSS(OS) 1 copy

Chief  
Livermore Division Fld Command DNA  
Lawrence National Laboratory  
P. O. Box 808  
Livermore, CA 94550

Attn: FCPRL 1 copy

National Technical Information Service  
U.S. Department of Commerce  
5254 Port Royal Road  
Springfield, VA 22161

24 copies

Commander  
BMC System Command  
P. O. Box 1550  
Huntsville, AL 35897

Attn: SSC-TEN 1 copy

DEP Chief of Staff for RSCH DEV & ACQ  
Department of the Army  
Washington, DC 20310

Attn: DANA-CSM-R 1 copy

Commander  
Perry Diamond Laboratories  
2805 Powder Mill Road  
Adelphi, MD 20763  
(CNSA)-INTEK ENVELOPE: ATTN: DELTD-BRH)

Attn: DELTD-BP 1 copy  
DELTD-RCC J. A. Rosale 1 copy  
DELTD-RCA P. A. Caldwell 1 copy  
DELTD-RCH D. Schellhorn 1 copy  
DELTD-TL Tech Lib. 1 copy  
S. Graybill 1 copy

Commander  
Picatinny Arsenal  
Dover, NJ 07801

Attn: SCAPA RD H-F 1 copy

Commander  
U. S. Army Missile Command  
Redstone Arsenal, AL 35809

Attn: Redstone Scientific Information CTR  
DRCFN-PM-PE-EA 1 copy

Commander  
U. S. Army Nuclear Agency  
7500 Backlick Road  
Building 2073  
Springfield, VA 22150

Attn: ATCN-U 1 copy

Commander  
U. S. Army Test and Evaluation COMD  
Aberdeen Proving Ground, MD 21005

Attn: DRSTE-EL 1 copy

Commander  
Naval Electronic Systems CMO HQS  
Washington, DC 20360

Attn: Code 5032 1 copy

Commanding Officer  
Naval Intelligence Support Center  
4301 Suitland Road - Building 5  
Washington, DC 20380

Attn: NISC-45 1 copy

Naval Research Laboratory  
Address: Attn: Name/Code  
Code 2623 - TIC-Distribution 25 copies  
Code 4600 - J. Boris 1 copy  
Code 4602 - D. Regel 1 copy  
Code 4700 - T. Coffey 25 copies  
Code 4707 - J. Davis 1 copy  
Code 4720 - S. Podetz 1 copy  
Code 4740 - V. Granatstein 1 copy  
Code 4740 - B. Ruben 1 copy  
Code 4761 - C. Katschmakos 1 copy  
Code 4770 - Branch Head 10 copies  
Code 4770 - F. Young 1 copy  
Code 4770 - S. Stephanchik 1 copy  
Code 4771 - B. Masten 10 copies  
Code 4773 - G. Comperstein 10 copies  
Code 4780 - B. Colsonant 1 copy  
Code 4780 - L. Huber 1 copy  
Code 4790 - M. Lampe 1 copy

On-Site Contractors:  
Code 4770 - P. Barker (Jaycor) 1 copy  
Code 4770 - S. Goldstein (Jaycor) 1 copy  
Code 4770 - R. Meyer (Jaycor) 1 copy  
Code 4770 - P. Uttinger (Jaycor) 1 copy  
Code 4770 - F. Sander (Jaycor) 1 copy  
Code 4790 - A. Drobot (Sol) 1 copy

Officer-in-Charge  
Naval Surface Weapons Center  
White Oak, Silver Spring, MD 20910

Attn: Code 4573 1 copy  
Code 4501 - Navy Nuc Progs Off 1 copy

Chief of Naval Operations  
Navy Department  
Washington, DC 20350

Attn: R. A. Blaise 00554 1 copy

Commander  
Naval Weapons Center  
China Lake, CA 93555

Attn: Code 133 Tech Lib. 1 copy

**AF Weapons Laboratory, AFSC**  
Kirtland AFB, NM 87117

Attn: CA 1 copy  
ELC 1 copy  
NT 1 copy  
SUL 1 copy  
DYP 1 copy  
J. Darrah 1 copy  
W.L. Baker 1 copy

HQ USAF/AFD  
Washington, DC 20330

Attn: RQCS 1 copy

Director  
Joint Staff J3 Planning Staff JCS  
OFFICE AFPL  
Owens, MD 20413

Attn: JSCS 1 copy

SAMSQ/RY  
Post Office Box 42966  
Worldway Postal Center  
Los Angeles, CA 90049  
(Technology)

Attn: D S 1 copy

SAMSQ/IN  
Post Office Box 42966  
Worldway Postal Center  
Los Angeles, CA 90049

Attn: INO MAJ D. S. Maskin 1 copy

SAMSQ/TH  
Norton AFB, CA 92403  
(Minuteman)

Attn: MMBH 1 copy

SAMSQ/SK  
Post Office Box 92960  
Worldway Postal Center  
Los Angeles, CA 90049  
(Space Coin Systems)

Attn: SKF P. H. Stadler 1 copy

U. S. Department of Energy  
Division of Inertial Fusion  
Washington, DC 20545

Attn: G. Canavan 1 copy  
T. F. Goddard 1 copy  
S. L. Kallias 1 copy  
R. L. Schrieffer 1 copy

Argonne National Laboratory  
9700 South Cass Avenue  
Argonne, Illinois 60439

Attn: G. R. Haggelssen 1 copy  
R. J. Martin 1 copy

Brookhaven National Laboratory  
Upton, NY 11973

Attn: A. F. Maschke 1 copy

Lawrence Berkeley Laboratory  
Berkeley, CA 94720

Attn: D. Knufe 1 copy

**Lawrence Livermore National Laboratory**  
P. O. Box 808  
Livermore, CA 94550

Attn: L-18 1 copy  
L-153 1 copy  
R. O. Bangerter 1 copy  
R. J. Briggs 1 copy  
E. P. Lee 1 copy  
J. H. Nuckolls 1 copy  
S. S. Yu 1 copy  
Tech Info Dept. L-3 1 copy

Los Alamos National Laboratory  
P. O. Box 1663  
Los Alamos, NM 87545

Attn: D. B. Henderson 1 copy  
K. B. Perkins 1 copy  
L. E. Thode 1 copy

National Science Foundation  
Mail Stop 19  
Washington, DC 20550

Attn: D. Benley 1 copy

Sandia National Laboratories  
P. O. Box 5800  
Albuquerque, NM 87115

Attn: J. R. Freeman 1 copy  
S. Humphries 1 copy  
D. J. Johnson 1 copy  
G. W. Kuwa 1 copy  
P. S. Miller 1 copy  
J. P. Vandevanter 1 copy  
G. Yonas 1 copy  
Doc Con for 3141 Sandia RPI Cell 1 copy

AVCO Research and Systems Group  
201 Low 11 Street  
Wilmingon, DE 19807

Attn: Research Lib. ARSO Rm. 7201 1 copy

BDM Corporation, Inc.  
795 Jones Branch Drive  
McLean, VA 22101

Attn: Tech Lib. 1 copy

Boeing Company, The  
P. O. Box 3107  
Seattle, WA 98124

Attn: Aerospace Library 1 copy

Cornell University  
Ithaca, NY 14850

Attn: D. A. Hamann 1 copy  
R. R. Sudan 1 copy  
J. Mainchen 1 copy

Dikewood Industries, Inc.  
1009 Broadway Drive, SE  
Albuquerque, NM 87106

Attn: L. W. Davis 1 copy

EG&G, Inc.  
Albuquerque Division  
P. O. Box 1418  
Albuquerque, NM 87114

Attn: Technical Library 1 copy

Ford Aerospace & Communications Operations  
Ford & Jamboree Roads  
Newport Beach, CA 92663  
(Formerly Aeronutronic Ford Corporation)

Attn: Tech Info Section 1 copy

Ford Aerospace & Communications Corp  
3939 Fabian Way  
Palo Alto, CA 94303  
(Formerly Aeronutronic Ford Corporation)

Attn: Library 1 copy  
D. R. McMorrow MS G 30 1 copy

General Electric Company  
Space Division  
Valley Forge Space Center  
Goddard Blvd., King of Prussia  
P. O. Box 8555  
Philadelphia, PA 19101

Attn: J. C. Penlen WFSC, Rm. 4230M 1 copy

General Electric Company  
Tempo-Center for Advanced Studies  
816 State Street (P. O. Drawer C6)  
Santa Barbara, CA 93102

Attn: DASIAC 1 copy

Grumman Aerospace Corporation  
Bethpage, NY 11714

Attn: P. Suh 1 copy

Institute for Defense Analyses  
401 Army-Navy Drive  
Arlington, VA 22202

Attn: IDA Librarian R. S. Smith 1 copy

Ion Physics Corporation  
South Bedford Street  
Easton, MA 01803

Attn: H. Hilde 1 copy

ISI Corporation  
P. O. Box 81027  
San Diego, CA 92138

Attn: R. L. Mertz 1 copy

JAYCOR, Inc.  
205 S. Whiting Street  
Alexandria, VA 22304

Attn: J. Guillory 1 copy  
R. Hubbard 1 copy  
R. Sullivan 1 copy  
D. A. Tidman 1 copy

JAYCOR, Inc.  
1401 Camino Del Mar  
Del Mar, CA 92014

Attn: E. Wenzes 1 copy

JAYCOR, Inc.  
390 Unicorn Park Drive  
Mebane, MA 01501

Attn: H. Linnerud 1 copy

Kaman Science Corporation  
P. O. Box 7463  
Colorado Springs, CO 80933

Attn: A. P. Bridges 1 copy  
D. H. Bryce 1 copy  
J. R. Hoffman 1 copy  
W. E. Ware 1 copy

Lockheed Missiles and Space Co., Inc.  
3251 Hanover Street  
Palo Alto, CA 94304

Attn: L. F. Chase 1 copy

Massachusetts Institute of Technology  
Cambridge, MA 02139

Attn: R. C. Davidson 1 copy  
G. Boloff 1 copy  
D. Hinchwood 1 copy

Maxwell Laboratories, Inc.  
9244 Balboa Avenue  
San Diego, CA 92123

Attn: R. W. Clark 1 copy  
A. C. Koth 1 copy  
P. Korn 1 copy  
A. R. Hillier 1 copy  
J. Pearlman 1 copy

McDonnell Douglas Corporation  
5301 Bolsa Avenue  
Huntington Beach, CA 92647

Attn: S. Schneider 1 copy

Mission Research Corporation  
1400 San Mateo Blvd. SE  
Albuquerque, NM 87108

Attn: B. B. Godfrey 1 copy

Mission Research Corporation-San Diego  
P. O. Box 1203  
LaJolla, CA 92038

Attn: V.A.J. Van Lint 1 copy

Mission Research Corporation  
735 State Street  
Santa Barbara, CA 93101

Attn: W. C. Hart 1 copy  
C. L. Longmire 1 copy

Northrop Corporation  
Electronic Division  
2301 West 120th Street  
Hawthorne, CA 90250

Attn: V. R. DeMartino 1 copy

Northrop Corporation  
Northrop Research and Technology Ctr.  
3401 West Broadway  
Hawthorne, CA 90250

Attn: S. Jones 1 copy

Physical Dynamics  
P.O. Box 556  
La Jolla, CA 92037

Attn: S. Jones 1 copy



Physics International Co.  
2700 Merced Street  
San Leandro, CA 94577

Attn: J. Benford 1 copy  
B. Bernstein 1 copy  
G. Frazier 1 copy  
R. Genuario 1 copy  
E. B. Goldman 1 copy  
R. Huff 1 copy  
A. J. Toepfer 1 copy

Pulsar Associates, Inc.  
11491 Sorrento Valley Blvd.  
San Diego, CA 92121

Attn: C. H. Jones, Jr. 1 copy

Princeton Plasma Physics Laboratory  
James Forrestal Campus  
P.O. Box 451  
Princeton, N.J. 08540

Attn: R. Kulsrud 1 copy

Pulse Sciences, Inc.  
1615 Broadway, Suite 610  
Oakland, CA 94612

Attn: I. Smith 1 copy  
P. Spence 1 copy  
S. Putnam 1 copy

R&D Associates  
P. O. Box 9695  
Marina Del Rey, CA 90291

Attn: W. R. Graham, Jr. 1 copy  
H. Grover 1 copy  
C. MacDonald 1 copy  
E. Martinelli 1 copy

R&D Associates  
Suite 503  
1401 Wilson Blvd.  
Arlington, VA 22209

Attn: P. J. Turchi 1 copy

Science Applications, Inc.  
P. O. Box 2351  
LaJolla, CA 92032

Attn: J. Robert Beyster 1 copy

Spire Corporation  
P. O. Box D  
Bedford, MA 01730

Attn: R. G. Little 1 copy

SRI International  
333 Ravenswood Avenue  
Menlo Park, CA 94025

Attn: Setsuo Odairiki 1 copy

Stanford University  
SLAC  
P. O. Box 4349  
Stanford, CA 94305

Attn: W. B. Hartmannsfeldt 1 copy

Systems, Science and Software, Inc.  
P. O. Box 1620  
LaJolla, CA 92038

Attn: A. R. Wilson 1 copy

Texas Tech University  
P. O. Box 5604 North College Station  
Lubbock, TX 79417

Attn: T. L. Simpson 1 copy

TRW Defense and Space Sys Group  
One Space Park  
Redondo Beach, CA 90278

Attn: Tech Info Center/S-1930 1 copy  
Z.G.T. Guiragossian 1 copy  
D. Amush 1 copy

University of California  
Dept. of Physics  
La Jolla, CA 92037

Attn: E. Brueckner 1 copy  
M.B. Thompson 1 copy

University of California  
Boelter Hall 7731  
Los Angeles, CA 90024

Attn: F.F. Chen 1 copy

University of California  
Irvine, CA 92624

Attn: G. Benford 1 copy  
H. Rostker 1 copy

University of Illinois  
Urbana, IL 61801

Attn: G. H. Wiley 1 copy  
J. T. Verdeyen 1 copy

University of Rochester  
Laboratory of Laser Energy  
River Station, Poppen 110  
Rochester, NY 14627

Attn: M. J. Lubin 1 copy

University of Scranton  
Dept. of Physics  
Scranton, PA 18510

Attn: F. Burney 1 copy

U. S. Department of Energy  
P. O. Box 60  
Oak Ridge, TN 37830

50 copies

Vought Corporation  
Michigan Division  
38111 Van Dyke Road  
Sterling Heights, MI 48077  
(Formerly ITV Aerospace Corp)

Attn: Tech Lib 1 copy

Atomic Weapons Research Establishment  
Building 10  
Aldermaston, Reading RG7 4FR  
United Kingdom

Attn: J. C. Martin 1 copy

Bhabha Atomic Research Centre  
Bombay - 400085, India

Attn: B. K. Godwal 1 copy  
A. S. Paithankar 1 copy

CEA, Centre de Etudes de Lemeil  
B. P. 27  
94190 Villeneuve, Saint George  
France

Attn: A. Bernard 1 copy  
A. Jolas 1 copy

CEA, Centre de Etudes de Valduc  
P. B. 14  
21120 Is-sur-Tille  
France

Attn: J. Barbare 1 copy  
C. Bruno 1 copy  
N. Camarcat 1 copy  
C. Patou 1 copy  
C. Peugeot 1 copy

Centro Di Frascati  
C.P.N. 65  
00044 Frascati (Rome)  
Italy

Attn: J.P. Rajer

Culham Laboratories  
UKAEA  
Eggington, Bils.  
England

Attn: N. J. Peacock 1 copy

Ecole Polytechnique  
Labo. PM  
91128 Palaiseau Cedex  
France

Attn: J. M. Euzzi 1 copy  
H. Doucet 1 copy

Ecole Polytechnique  
Labo. PM  
91128 Palaiseau Cedex  
France

Attn: J.M. Euzzi 1 copy  
H. Doucet 1 copy

Institut d'Electronique Fondamentale  
Universite' Paris XI-Orsay  
F91405 Orsay  
France

Attn: G. Gautherin 1 copy

Institut fur Angewandte Physik  
Robert Mayer Str. 2-4  
D6000 Frankfurt,  
West Germany

Attn: H. Dettlinghoff 1 copy  
H. Klein 1 copy

Institut Fur Neutronenphysik  
an Reaktor Technik  
Postfach 3640  
Kernforschungszentrum  
D-7500 Karlsruhe 1  
West Germany

Attn: H. Blum 1 copy  
H. U. Karow 1 copy  
W. Schmidt 1 copy  
K.W. Zieher 1 copy

Institute of Atomic Energy  
Academia Sinica  
P.O. Box 2125  
Beijing  
People's Republic of China

Attn: H. Ganchang, Director 2 copies  
R. Hong 1 copy

Institute of Laser Engineering  
Osaka University  
Yamada-ken  
Suita  
Osaka 565, Japan

Attn: K. Imasaki 1 copy  
S. Ikei 1 copy

Instituto De Investigaciones Cientificas Y Tecnicas  
De Las Fuerzas Armadas  
Aerofratergi y Vuela  
V. Martelli 1603  
Pcia Bs. As. - R. Argentina

Attn: R. R. Canusso 1 copy

Max-Planck-Institut fur Plasmaphysik  
8046 Garching bei Munchen  
West Germany

Attn: R. Lengyel 1 copy  
I. Hofmann 1 copy

Physical Research Laboratory  
Navrangpura  
Ahmedabad - 380009 - India

Attn: V. Ramani 1 copy  
P. I. Jain 1 copy

Shivaji University  
Kolhapur, India

Attn: L. N. Katkan 1 copy

Tokyo Institute of Technology  
The Graduate School at Nagatsuta  
4259 Nagatsuta, Midori-Ku  
Yokohama 227, Japan

Attn: K. Iku 1 copy  
S. Yamaguchi 1 copy

Weizmann Institute of Science  
Rehovot, Israel

Attn: A. E. Bleugrund 1 copy  
E. Herdi 1 copy  
Z. Zircmon 1 copy

Bechtel Group, Inc.  
P. O. Box 5465  
San Francisco, CA 94119

Attn: William O. Allen 1 copy

DATE  
FILMED  
-8